

# SASSO 60 round adjustable

ceiling

048-31102119S



Project / Type

Notes

Count / Date



## General

Ceiling , Surface

tilt max 30°

rotation 360°

black , RAL 9005 <sup>1</sup>

Inner colour gold

IP20

734 lm

## LED

3500 K

CRI ≥ 90

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 90 , R<sub>(1-15)</sub>: 89

MR 0.7

MDER 0.64

## Optical

spot

beam angle 15°

UGR ≤ 13

## Electrical

non DIM

220-240 V

system 10.4 W

system 71 lm/W<sup>2</sup>

PC1


## Physical

diameter 72 mm


height 108 mm

0.5 kg

## Light distribution



## Product drawing



<sup>1</sup> RAL code

<sup>2</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Installation instructions



## Lighting calculator



SASSO 60 round adjustable ceiling 048-31102119S



Project / Type

Notes

Count / Date

Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10                            | 10                 |
| B16                            | 17                 |
| B20                            | 20                 |
| C10                            | 16                 |
| C16                            | 27                 |
| C20                            | 33                 |

