

SASSO 40 round wallwasher

trimless

048-2840219A 048-2896117 002-90744



Project / Type

Notes

Count / Date



General

Ceiling | Recessed
 rotation 360°
 gold | RAL 260-M ¹
 Mounting set traffic white
 IP20
 457 lm
 fixture 73 lm/W ²

LED

3500 K
 CRI ≥ 90
 L90 / 50000 h
 MR 0.82 | MDER 0.74

Optical

wallwasher | beam angle 118°
 PstLM ≤ 1.0 ³ | SVM ≤ 0.4 ³

Electrical

non DIM
 PC2 | 220-240 V
 system 7.6 W | fixture 6.3 W
 36 Vf | 200 mA

Physical

trimless
 diameter 56 mm | height 55 mm
 0.61 kg

Cutout

diameter 56 mm
 recessed depth 60 mm


¹ RAL code

² incl. consideration of optical losses & internal control unit losses


³ Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; surface gold; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 12.5/15/25 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 3500 K; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2; 220-240 V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator

