

# SASSO 100 round wallwasher/floor

trim

048-2740119W 048-2796317 002-90767



Project / Type

Notes

Count / Date



General
Ceiling   Recessed
rotation 360°
gold   RAL 260-M <sup>1</sup>
Mounting set traffic white
IP20
2060 lm
fixture 141 lm/W <sup>2</sup>


LED
4000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 98   R <sub>r</sub> : 90   R <sub>t(1-15)</sub> : 88
MR 0.8   MDER 0.72

Optical
wallwasher floor
PstLM ≤ 1.0 <sup>3</sup>   SVM ≤ 0.4 <sup>3</sup>


Electrical
DALI-2
PC2   220-240 V
system 17.2 W   fixture 14.6 W
36 Vf   450 mA

Physical
trim
diameter 118 mm   height 96 mm
0.68 kg

## Light distribution



## Product drawing



Cutout
diameter 108 mm
min. ceiling thickness 2 mm   max. ceiling thickness 25 mm
recessed depth 100 mm

<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses  
<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

