

048-2740911W 048-2796198 002-90767



Project / Type

Notes

Count / Date



Ceiling | Recessed

rotation 360°

black | RAL 9005 ¹

IP20

1870 lm

fixture 128 lm/W²

2700 K

CBI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_q: 97 | R_f: 91 | R_{1-15}: 87

MR 0.52 | MDER 0.47

wallwasher floor

$$\text{PstLM} \leq 1.0^3 \mid \text{SVM} \leq 0.4^3$$

DAI I-2

PC2 | 220-240 V

system 17.2 W | fixture 14.6 W

36 Vf | 450 mA

trimless for acoustic ceiling

diameter 114 mm | height 96 mm

0.76 kg

diameter 100-102 mm

min. ceiling thickness 25 mm | max. ceiling thickness 40 mm

recessed depth 100 mm



Round recessed spotlight in die-cast aluminium; 1 lamp; surface black; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; for trimless installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2; 220-240 V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;