

# SASSO 60 round adjustable

trimless exposed concrete

048-2622111S 048-2695210 002-90790



Project / Type

Notes

Count / Date



General
Ceiling   Recessed
tilt max 30°
rotation 360°
black   RAL 9005 <sup>1</sup>
Mounting set white aluminium
front IP40   back IP20
874 lm
fixture 80 lm/W <sup>2</sup>

LED
4000 K
CRI ≥ 90
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 98   R <sub>r</sub> : 90   R <sub>t(1-15)</sub> : 88
MR 0.8   MDER 0.72


Optical
spot   beam angle 15°
UGR ≤ 13
PstLM ≤ 1.0 <sup>3</sup>   SVM ≤ 0.4 <sup>3</sup>

Electrical
DALI-2   1 DALI Addr.
PC2   220-240 V
system 12.8 W   fixture 10.9 W
36 Vf   300 mA

Physical
trimless for exposed concrete ceiling
length 230 mm   width 230 mm   height 162 mm
6.8 kg

Cutout
recessed depth 120 mm

## Light distribution



## Product drawing



<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses  
<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

