


# SASSO 60 round adjustable trim soft acoustic ceiling

048-2622011F 048-2696397 002-90790



Project / Type \_\_\_\_\_  
 Notes \_\_\_\_\_  
 Count / Date \_\_\_\_\_



## General

Ceiling | Recessed  
 tilt max 30°  
 rotation 360°  
 black | RAL 9005 <sup>1</sup>  
 Mounting set traffic white  
 front IP40 | back IP20  
 877 lm  
 fixture 82 lm/W <sup>2</sup>

## LED

3000 K  
 CRI ≥ 90  
 L80 / 50000 h  
 initial MacAdam ≤ 2 SDCM  
 R<sub>g</sub>: 99 | R<sub>r</sub>: 90 | R<sub>[1-15]</sub>: 87  
 MR 0.6 | MDER 0.54

## Optical

flood | beam angle 40°  
 UGR ≤ 19 | ≥65° <1500 cd/m<sup>2</sup>  
 PstLM ≤ 1.0 <sup>3</sup> | SVM ≤ 0.4 <sup>3</sup>

## Electrical

DALI-2 | 1 DALI Addr.  
 PC2 | 220-240 V  
 system 12.5 W | fixture 10.6 W  
 36 Vf | 300 mA

## Physical

with trim for acoustic ceiling  
 diameter 80 mm | height 48 mm  
 4.7 kg


## Cutout

diameter 74 mm  
 min. ceiling thickness 25 mm | max. ceiling thickness 40 mm  
 recessed depth 100 mm


<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses  
<sup>3</sup> Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface black; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim traffic white; for installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 40° beam; UGR ≤ 19; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m<sup>2</sup>; degree of protection from below IP40 (from above IP20); PC2; 220-240 V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

