

SASSO 60 round adjustable trimless soft acoustic ceiling

048-2622014F 048-2696197 002-90790



Project / Type

Notes

Count / Date




| |
|------------------------------|
| General |
| Ceiling Recessed |
| tilt max 30° |
| rotation 360° |
| matt silver |
| Mounting set traffic white |
| front IP40 back IP20 |
| 1010 lm |
| fixture 95 lm/W ¹ |

| |
|---|
| LED |
| 3000 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 99 R _f : 90 R _{f(1-15)} : 87 |
| MR 0.6 MDER 0.54 |


| |
|---|
| Optical |
| flood beam angle 40° |
| UGR ≤ 19 ≥65° <1500 cd/m ² |
| PstLM ≤ 1.0 ² SVM ≤ 0.4 ² |

Round recessed spotlight in die-cast aluminium; 1 lamp; surface matt silver; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; traffic white; for trimless installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 40° beam; UGR ≤ 19; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; degree of protection from below IP40 (from above IP20); PC2; 220-240 V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



| |
|--------------------------------|
| Electrical |
| DALI-2 1 DALI Addr. |
| PC2 220-240 V |
| system 12.5 W fixture 10.6 W |
| 36 Vf 300 mA |

| |
|-------------------------------|
| Physical |
| trimless for acoustic ceiling |
| diameter 80 mm height 48 mm |
| 5 kg |

| |
|---|
| Cutout |
| diameter 74 mm |
| min. ceiling thickness 25 mm max. ceiling thickness 40 mm |
| recessed depth 120 mm |

¹ incl. consideration of optical losses & internal control unit losses
² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator



SASSO 60 round adjustable trimless soft acoustic ceiling

048-2622014F 048-2696197 002-90790



Project / Type

Notes

Count / Date

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF | 0.964 | 0.923 | 0.884 | 0.847 | 0.811 |
| LSF | 1 | 1 | 1 | 1 | 1 |
| MF | LMF × RSMF × LLMF × LSF | | RSMF ^a | Room Surface Maintenance Factor | |
| MF | Maintenance Factor | | LLMF | Lamp Lumens Maintenance Factor | |
| LMF ^a | Luminaire Maintenance Factor | | LSF | Lamp Survival Factor | |

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10 | 72 |
| B16 | 115 |
| C10 | 106 |
| C16 | 170 |

Components

MOUNTING SET trimless for soft acoustic ceilings

| | | |
|---------------|--------|-------------------|
| COLOUR | Ø (MM) | ARTICLE NUMBER(S) |
| traffic white | 80 | 048-2696197 |

POWER SUPPLY

| |
|-------------------|
| ARTICLE NUMBER(S) |
| 002-90790 |

Mounting accessories

MOUNTING TOOL

| | | |
|---------------|------------|-------------------|
| COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
| traffic black | 77-77-35 | 048-2695918 |



Optional electrical accessories

DIN RAIL LED DRIVER

| | | |
|-------------------------|------------|-------------------|
| TYPE | L-W-H (MM) | ARTICLE NUMBER(S) |
| 200 - 1050 mA 2 x 42W | 36-88-59 | 005-6121030 |



DIN RAIL POWER SUPPLY

| | |
|------------|-------------------|
| L-W-H (MM) | ARTICLE NUMBER(S) |
| 72-90-63 | 005-6520210 |



Optional electrical accessories

POWER SUPPLY PREWIRED

| | |
|-------------------|-------------------|
| TYPE | ARTICLE NUMBER(S) |
| with junktion box | 002-90790A |
| with junktion box | 002-90748A |
| with junktion box | 002-90771A |
| with junktion box | 002-90742A |



SASSO 60 round adjustable trimless soft acoustic ceiling

048-2622014F 048-2696197 002-90790



Project / Type

Notes

Count / Date

Optional electrical accessories

POWER SUPPLY

| TYPE | L-W-H (MM) | ARTICLE NUMBER(S) |
|----------------------------|------------|-------------------|
| with loop through function | 185-30-21 | 002-90770 |
| with loop through function | 185-30-21 | 002-90747 |

