

SASSO 60 round downlight


trim

048-2602219S 048-269631G 002-90790



Round recessed spotlight in die-cast aluminium; 1 lamp; surface gold; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim white aluminium; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3500 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 15° beam; UGR ≤ 13 ; degree of protection from below IP44 (from above IP20); PC2; 220-240 V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Project / Type	
Notes	
Count / Date	



General

Ceiling , Recessed	
rotation 360°	
gold , RAL 260-M ¹	
Mounting set white aluminium	
front IP44 , back IP20	
901 lm	
fixture 83 lm/W ²	

LED

3500 K	
CRI ≥ 90	
initial MacAdam ≤ 2 SDCM	
R _g : 99 , R _f : 90 , R ₍₁₋₁₅₎ : 87	
MR 0.6	
MDER 0.54	

Optical

spot	
beam angle 15°	
UGR ≤ 13	
PstLM ≤ 1.0 ³	
SVM ≤ 0.4 ³	

Electrical

DALI-2	
220-240 V	
system 12.8 W	
fixture 10.9 W	
36 Vf	
300 mA	
PC2	
1 DALI Addr.	

Physical

trim	
diameter 80 mm	
height 48 mm	
4.7 kg	

Cutout

diameter 73 mm	
min. ceiling thickness 2 mm	
max. ceiling thickness 25 mm	
recessed depth 110 mm	

¹ RAL code
² incl. consideration of optical losses & internal control unit losses
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

