

SASSO 60 round wallwasher

semi-recessed

048-3701174A 002-90748



Project / Type


Notes

Count / Date



Cylindrical semi-recessed spotlight made of aluminium; surface white powder coated; Inner colour lacquered in matt silver; 360° rotatable; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; degree of protection IP20; PC2; 220-240 V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); external converter for ceiling insertion, through-wiring suitable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

| |
|-------------------------------|
| Ceiling Semi-Recessed |
| rotation 360° |
| white RAL 9016 ¹ |
| Inner colour matt silver |
| IP20 |
| 650 lm |
| fixture 80 lm/W ² |

LED

| |
|---|
| 4000 K |
| CRI ≥ 90 |
| L90 / 50000 h |
| initial MacAdam ≤ 3 SDCM |
| R _g : 102 R _f : 93 R _{f(1-5)} : 92 |
| MR 0.81 MDER 0.74 |

Optical

| |
|---|
| wallwasher |
| PstLM ≤ 1.0 ³ SVM ≤ 0.4 ³ |

Electrical

| |
|------------------------------|
| DALI-2 |
| PC2 220-240 V |
| system 9.5 W fixture 8.1 W |
| 36 Vf 250 mA |

Physical

| |
|-------------------------------|
| diameter 72 mm height 75 mm |
| 0.48 kg |

Cutout

| |
|-----------------------|
| diameter 60 mm |
| recessed depth 110 mm |

¹ RAL code
² incl. consideration of optical losses & internal control unit losses
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

