

# SASSO 60 round wallwasher trim soft acoustic ceiling

048-2641911A 048-2696398 002-90748



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



|  |
|--|
| <b>General</b>                                   |
| Ceiling , Recessed                               |
| rotation 360°                                    |
| black , RAL 9005 <sup>1</sup>                    |
| Mounting set traffic black for acoustic ceilings |
| IP20   |
| 526 lm   |
| fixture 65 lm/W <sup>2</sup>                     |

|   |
|---|
| <b>LED</b>  |
| 2700 K  |
| CRI ≥ 90  |
| L90 / 50000 h   |
| initial MacAdam ≤ 3 SDCM  |
| R <sub>g</sub> : 101 , R <sub>r</sub> : 91 , R <sub>(1-15)</sub> : 89 |
| MR 0.56   |
| MDER 0.51   |


|                          |
|--------------------------|
| <b>Optical</b>           |
| wallwasher               |
| PstLM ≤ 1.0 <sup>3</sup> |
| SVM ≤ 0.4 <sup>3</sup>   |

|                   |
|-------------------|
| <b>Electrical</b> |
| DALI-2            |
| 220-240 V         |
| system 9.5 W      |
| fixture 8.1 W     |
| 36 Vf             |
| 250 mA            |
| PC2               |
| 1 DALI Addr.      |


|                                |
|--------------------------------|
| <b>Physical</b>                |
| with trim for acoustic ceiling |
| diameter 80 mm                 |
| height 48 mm                   |

|                              |
|------------------------------|
| <b>Cutout</b>                |
| diameter 74 mm               |
| min. ceiling thickness 25 mm |
| max. ceiling thickness 40 mm |
| recessed depth 110 mm        |

## Light distribution



## Product drawing



<sup>1</sup> RAL code

<sup>2</sup> incl. consideration of optical losses & internal control unit losses

<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

