

# SASSO 60 round wallwasher trim soft acoustic ceiling

048-2641919A 048-2696397 002-90742



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_




|   |
|---|
| <b>General</b>                                  |
| Ceiling , Recessed                              |
| rotation 360°                                   |
| gold , RAL 260-M <sup>1</sup>                   |
| Mounting set signal white for acoustic ceilings |
| IP20  |
| 544 lm  |
| fixture 67 lm/W <sup>2</sup>                    |

|   |
|---|
| <b>LED</b>  |
| 2700 K  |
| CRI ≥ 90  |
| L90 / 50000 h   |
| initial MacAdam ≤ 3 SDCM  |
| R <sub>g</sub> : 101 , R <sub>r</sub> : 91 , R <sub>(1-15)</sub> : 89 |
| MR 0.56   |
| MDER 0.51   |


|                          |
|--------------------------|
| <b>Optical</b>           |
| wallwasher               |
| PstLM ≤ 1.0 <sup>3</sup> |
| SVM ≤ 0.4 <sup>3</sup>   |

Round recessed spotlight in die-cast aluminium; 1 lamp; surface gold; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim signal white for acoustic ceilings; for installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2; 220-240 V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



|                   |
|-------------------|
| <b>Electrical</b> |
| non DIM           |
| 220-240 V         |
| system 9.5 W      |
| fixture 8.1 W     |
| 36 Vf             |
| 250 mA            |
| PC2               |

|                                |
|--------------------------------|
| <b>Physical</b>                |
| with trim for acoustic ceiling |
| diameter 80 mm                 |
| height 48 mm                   |
| 0.24 kg                        |

|                              |
|------------------------------|
| <b>Cutout</b>                |
| diameter 74 mm               |
| min. ceiling thickness 25 mm |
| max. ceiling thickness 40 mm |
| recessed depth 60 mm         |

<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses  
<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

