

SASSO 60 round wallwasher trimless soft acoustic ceiling

048-2641219A 048-2696198 002-90742



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Recessed _____

rotation 360° _____

gold , RAL 260-M ¹ _____

Mounting set traffic black for acoustic ceilings _____

IP20 _____

591 lm _____

fixture 73 lm/W² _____

LED

3500 K _____

CRI ≥ 90 _____

L90 / 50000 h _____

MR 0.82 _____

MDER 0.74 _____

Optical

wallwasher _____

PstLM ≤ 1.0 ³ _____

SVM ≤ 0.4 ³ _____

Electrical

non DIM _____

220-240 V _____

system 9.5 W _____

fixture 8.1 W _____

36 Vf _____

250 mA _____

PC2 _____

Physical

trimless for acoustic ceiling _____

diameter 80 mm _____

height 48 mm _____

0.29 kg _____

Cutout


diameter 74 mm _____

min. ceiling thickness 25 mm _____


max. ceiling thickness 40 mm _____

recessed depth 60 mm _____

Light distribution



Product drawing



¹ RAL code

² incl. consideration of optical losses & internal control unit losses

³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

