

SASSO 60 round wallwasher trimless soft acoustic ceiling

048-2641214A 048-2696197 002-90748



Project / Type _____


Notes _____

Count / Date _____




Round recessed spotlight in die-cast aluminium; 1 lamp; surface matt silver; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; signal white for acoustic ceilings; for trimless installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 3500 K; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2; 220-240 V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Recessed _____

rotation 360° _____

matt silver _____

Mounting set signal white for acoustic ceilings _____

IP20 _____

625 lm _____

fixture 77 lm/W¹ _____

LED

3500 K _____

CRI ≥ 90 _____

L90 / 50000 h _____

MR 0.82 _____

MDER 0.74 _____

Optical

wallwasher _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____

220-240 V _____

system 9.5 W _____

fixture 8.1 W _____

36 Vf _____

250 mA _____

PC2 _____

1 DALI Addr. _____

Physical

trimless for acoustic ceiling _____

diameter 80 mm _____

height 48 mm _____

Cutout

diameter 74 mm _____

min. ceiling thickness 25 mm _____

max. ceiling thickness 40 mm _____

recessed depth 120 mm _____

¹ incl. consideration of optical losses & internal control unit losses

² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

