

SASSO 60 round wallwasher/floor trim soft acoustic ceiling

048-2641111W 048-2696397 002-90748



Project / Type	
Notes	
Count / Date	



General
Ceiling , Recessed
rotation 360°
black , RAL 9005 ¹
Mounting set signal white for acoustic ceilings
IP20
1060 lm
fixture 120 lm/W ²

LED
4000 K
CRI ≥ 90
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 99 , R _r : 92 , R ₍₁₋₅₎ : 90
MR 0.81
MDER 0.74

Optical
wallwasher floor
PstLM ≤ 1.0 ³
SVM ≤ 0.4 ³


Electrical
DALI-2
220-240 V
system 10.4 W
fixture 8.9 W
36 Vf
250 mA
PC2
1 DALI Addr.

Physical
with trim for acoustic ceiling
diameter 80 mm
height 48 mm


Cutout
diameter 74 mm
min. ceiling thickness 25 mm
max. ceiling thickness 40 mm
recessed depth 110 mm

Round recessed spotlight in die-cast aluminium; 1 lamp; surface black; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim signal white for acoustic ceilings; for installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2; 220-240 V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code
² incl. consideration of optical losses & internal control unit losses
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

