

# SASSO 60 round wallwasher trim soft acoustic ceiling

048-2641111A 048-2696397 002-90742



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



<b>General</b>
Ceiling , Recessed
rotation 360°
black , RAL 9005 <sup>1</sup>
Mounting set signal white for acoustic ceilings
IP20
594 lm
fixture 73 lm/W <sup>2</sup>

<b>LED</b>
4000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 102 , R <sub>r</sub> : 93 , R <sub>(1-15)</sub> : 92
MR 0.81
MDER 0.74


<b>Optical</b>
wallwasher
PstLM ≤ 1.0 <sup>3</sup>
SVM ≤ 0.4 <sup>3</sup>

<b>Electrical</b>
non DIM
220-240 V
system 9.5 W
fixture 8.1 W
36 Vf
250 mA
PC2


<b>Physical</b>
with trim for acoustic ceiling
diameter 80 mm
height 48 mm
0.24 kg

<b>Cutout</b>
diameter 74 mm
min. ceiling thickness 25 mm
max. ceiling thickness 40 mm
recessed depth 60 mm

## Light distribution



## Product drawing



<sup>1</sup> RAL code

<sup>2</sup> incl. consideration of optical losses & internal control unit losses

<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

