

SASSO 60 round wallwasher/floor trimless soft acoustic ceiling

048-2641019W 048-2696198 002-90748



Project / Type _____
 Notes _____
 Count / Date _____



General

Ceiling | Recessed
 rotation 360°
 gold | RAL 260-M ¹
 IP20
 1030 lm
 fixture 117 lm/W ²

LED

3000 K
 CRI ≥ 90
 L85 / 50000 h
 initial MacAdam ≤ 3 SDCM
 R_g: 99 | R_f: 91 | R_(f-15): 89
 MR 0.61 | MDER 0.55

Optical

wallwasher floor
 PstLM ≤ 1.0 ³ | SVM ≤ 0.4 ³

Electrical

DALI-2 | 1 DALI Addr.
 PC2 | 220-240 V
 system 10.4 W | fixture 8.9 W
 36 Vf | 250 mA

Physical

trimless for acoustic ceiling
 diameter 80 mm | height 48 mm
 0.33 kg


Cutout

diameter 74-76 mm
 min. ceiling thickness 25 mm | max. ceiling thickness 40 mm
 recessed depth 120 mm


¹ RAL code
² incl. consideration of optical losses & internal control unit losses
³ Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface gold; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; for trimless installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2; 220-240 V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator

