

# SASSO 60 round adjustable trim soft acoustic ceiling

048-2622214M 048-2696398 002-90771



Project / Type

Notes

Count / Date



|                               |
|-------------------------------|
| General                       |
| Ceiling   Recessed            |
| tilt max 30°                  |
| rotation 360°                 |
| matt silver                   |
| Mounting set jet black        |
| front IP40   back IP20        |
| 1100 lm                       |
| fixture 103 lm/W <sup>1</sup> |

|   |
|---|
| LED   |
| 3500 K  |
| CRI ≥ 90  |
| L80 / 50000 h   |
| initial MacAdam ≤ 2 SDCM  |
| R <sub>g</sub> : 99   R <sub>r</sub> : 90   R <sub>t(1-15)</sub> : 89 |
| MR 0.7   MDER 0.64  |

|   |
|---|
| Optical   |
| medium   beam angle 27°                           |
| UGR ≤ 16  |
| PstLM ≤ 1.0 <sup>2</sup>   SVM ≤ 0.4 <sup>2</sup> |

|                                |
|--------------------------------|
| Electrical                     |
| non DIM                        |
| PC2   220-240 V                |
| system 12.5 W   fixture 10.6 W |
| 36 Vf   300 mA                 |


|                                |
|--------------------------------|
| Physical                       |
| with trim for acoustic ceiling |
| diameter 80 mm   height 48 mm  |
| 0.33 kg                        |

|   |
|---|
| Cutout  |
| diameter 74 mm  |
| min. ceiling thickness 25 mm   max. ceiling thickness 40 mm |
| recessed depth 100 mm                                       |


<sup>1</sup> incl. consideration of optical losses & internal control unit losses  
<sup>2</sup> Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface matt silver; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim jet black; for installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3500 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 27° beam; UGR ≤ 16; degree of protection from below IP40 (from above IP20); PC2; 220-240 V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator



# SASSO 60 round adjustable trim soft acoustic ceiling

048-2622214M 048-2696398 002-90771



Project / Type

Notes

Count / Date

## Maintenance Factors

| Operating Time [h] | 10 000                       | 20 000 | 30 000            | 40 000                          | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF               | 0.964                        | 0.923  | 0.884             | 0.847                           | 0.811  |
| LSF                | 1                            | 1      | 1                 | 1                               | 1      |
| MF                 | LMF × RSMF × LLMF × LSF      |        | RSMF <sup>a</sup> | Room Surface Maintenance Factor |        |
| MF                 | Maintenance Factor           |        | LLMF              | Lamp Lumens Maintenance Factor  |        |
| LMF <sup>a</sup>   | Luminaire Maintenance Factor |        | LSF               | Lamp Survival Factor            |        |

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10                            | 43                 |
| B13                            | 55                 |
| B16                            | 68                 |
| B20                            | 85                 |
| C10                            | 72                 |
| C13                            | 94                 |
| C16                            | 116                |
| C20                            | 145                |

## Components

### MOUNTING SET trim for soft acoustic ceilings

|           |        |                   |
|-----------|--------|-------------------|
| COLOUR    | Ø (MM) | ARTICLE NUMBER(S) |
| jet black | 80     | 048-2696398       |

### POWER SUPPLY

|            |                   |
|------------|-------------------|
| L-W-H (MM) | ARTICLE NUMBER(S) |
| 85-40-22   | 002-90771         |



## Mounting accessories

### MOUNTING TOOL

|               |            |                   |
|---------------|------------|-------------------|
| COLOUR        | L-W-H (MM) | ARTICLE NUMBER(S) |
| traffic black | 77-77-35   | 048-2695918       |



## Optional electrical accessories

### DIN RAIL LED DRIVER

|                         |            |                   |
|-------------------------|------------|-------------------|
| TYPE                    | L-W-H (MM) | ARTICLE NUMBER(S) |
| 200 - 1050 mA   2 x 42W | 36-88-59   | 005-6121030       |



### DIN RAIL POWER SUPPLY

|            |                   |
|------------|-------------------|
| L-W-H (MM) | ARTICLE NUMBER(S) |
| 72-90-63   | 005-6520210       |



# SASSO 60 round adjustable trim soft acoustic ceiling

048-2622214M 048-2696398 002-90771



Project / Type

Notes

Count / Date

## Optional electrical accessories

### POWER SUPPLY PREWIRED

| TYPE              | ARTICLE NUMBER(S) |
|-------------------|-------------------|
| with junktion box | 002-90790A        |
| with junktion box | 002-90748A        |
| with junktion box | 002-90771A        |
| with junktion box | 002-90742A        |

## Optional electrical accessories

### POWER SUPPLY

| TYPE                       | L·W·H (MM) | ARTICLE NUMBER(S) |
|----------------------------|------------|-------------------|
| with loop through function | 185-30-21  | 002-90770         |
| with loop through function | 185-30-21  | 002-90747         |

