

SASSO 60 round adjustable trim soft acoustic ceiling

048-2622119M 048-2696397 002-90771



Project / Type


Notes

Count / Date



Round recessed spotlight in die-cast aluminium; 1 lamp; surface gold; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim traffic white; for installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 27° beam; UGR ≤ 16 ; degree of protection from below IP40 (from above IP20); PC2; 220-240 V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

| |
|-------------------------------|
| Ceiling Recessed |
| tilt max 30° |
| rotation 360° |
| gold RAL 260-M ¹ |
| Mounting set traffic white |
| front IP40 back IP20 |
| 1070 lm |
| fixture 100 lm/W ² |

LED

| |
|--|
| 4000 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 98 R _f : 90 R _{t-15} : 88 |
| MR 0.8 MDER 0.72 |

Optical

| |
|---|
| medium beam angle 27° |
| UGR ≤ 16 |
| PstLM ≤ 1.0 ³ SVM ≤ 0.4 ³ |

Electrical

| |
|--------------------------------|
| non DIM |
| PC2 220-240 V |
| system 12.5 W fixture 10.6 W |
| 36 Vf 300 mA |

Physical

| |
|--------------------------------|
| with trim for acoustic ceiling |
| diameter 80 mm height 48 mm |
| 0.28 kg |

Cutout

| |
|---|
| diameter 74 mm |
| min. ceiling thickness 25 mm max. ceiling thickness 40 mm |
| recessed depth 100 mm |

¹ RAL code
² incl. consideration of optical losses & internal control unit losses
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

