

SASSO 60 round adjustable trimless soft acoustic ceiling

048-2622111F 048-2696197 002-90771



Project / Type

Notes

Count / Date



General

Ceiling Recessed
tilt max 30°
rotation 360°
jet black RAL 9005
Mounting set traffic white
front IP40 back IP20
915 lm
fixture 86 lm/W ¹

LED

4000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R _g : 98 R _f : 90 R _[1-15] : 88
MR 0.8 MDER 0.72

Optical

flood beam angle 40°
UGR ≤ 19 ≥65° <1500 cd/m²
PstLM ≤ 1.0 ² SVM ≤ 0.4 ²

Electrical

non DIM
PC2 220-240 V
system 12.5 W fixture 10.6 W
36 Vf 300 mA

Physical


trimless for acoustic ceiling
diameter 80 mm height 48 mm
0.63 kg

Cutout


diameter 74 mm
min. ceiling thickness 25 mm max. ceiling thickness 40 mm
recessed depth 120 mm

¹ incl. consideration of optical losses & internal control unit losses
² Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator

