

# SASSO 60 round adjustable

trim

048-2622014S 048-269631G 002-90771



Project / Type

Notes

Count / Date



General
Ceiling   Recessed
tilt max 30°
rotation 360°
matt silver
Mounting set white aluminium
front IP40   back IP20
898 lm
fixture 83 lm/W <sup>1</sup>

LED
3000 K
CRI ≥ 90
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 99   R <sub>r</sub> : 90   R <sub>f(1-5)</sub> : 87
MR 0.6   MDER 0.54

Optical
spot   beam angle 15°
UGR ≤ 13
PstLM ≤ 1.0 <sup>2</sup>   SVM ≤ 0.4 <sup>2</sup>


Electrical
non DIM
PC2   220-240 V
system 12.8 W   fixture 10.9 W
36 Vf   300 mA

Physical
trim
diameter 80 mm   height 48 mm
0.28 kg


Cutout
diameter 73 mm
min. ceiling thickness 2 mm   max. ceiling thickness 25 mm
recessed depth 60 mm

<sup>1</sup> incl. consideration of optical losses & internal control unit losses  
<sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

