SASSO 60 round downlight

trimless exposed concrete

048-2602217S 048-2695210 002-90771

Project / Type

Notes

Count / Date

Round recessed spotlight in die-cast aluminium; 1 lamp; surface white; installation without tools in mounting set due to patented ball catch system; concrete housings for exposed concrete ceilings; for trimless installation; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3500 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 15° beam; UGR ≤ 19; degree of protection from below IP44 (from above IP20); PC2; 220-240 V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing





General

Ceiling , Recessed
rotation 360°
white , RAL 9016 [1]
Mounting set white aluminium
front IP44 , back IP20
945 lm
fixture 87 lm/W[2]

LED

3500 K
CRI ≥ 90
initial MacAdam ≤ 2 SDCM
R_g: 99 , R_f: 90 , $R_{f1\text{-}15}$: 87
MR 0.6
MDER 0.54

Optical

spot
beam angle 15°
UGR ≤ 19
PstLM ≤ 1.0 [3]
SVM ≤ 0.4 [3]

Electrical

non DIM
220-240 V
system 12.8 W
fixture 10.9 W
36 Vf
300 mA
PC2

Physical

trimless for exposed concrete ceiling
length 230 mm
width 230 mm
height 162 mm
2.37 kg

Cutout

recessed depth 90 mm

[1] RAL code
[2] incl. consideration of optical losses & internal control unit losses
[3] Value of containing product at full load (undimmed)

Installation instructions

Lighting calculator

['048-2602217S 048-2695210 002-90771'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com