

SASSO 100 round downlight

suspended

048-34202317S



Project / Type

Notes

Count / Date



General

Ceiling | Suspended

jet black | RAL 9005 ¹

Inner colour white

IP20

1510 lm

LED

3500 K

CRI \geq 90

L80 / 50000 h

initial MacAdam \leq 2 SDCM

R_g: 99 | R_r: 90 | R_{t(1-15)}: 89

MR 0.7 | MDER 0.64

Optical

spot | beam angle 19°

UGR \leq 19

Electrical

DALI-2 | 1 DALI Addr.

PC1 | 220-240 V

system 17.9 W

system 84 lm/W ²

Physical

diameter 100 mm | height 115 mm


1.3 kg

¹ RAL code


² incl. consideration of optical losses, internal control unit losses
& operating device efficiency

Cylindrical spotlight in die-cast aluminium; surface jet black powder coated; Inner colour lacquered in white; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3500 K; binning initial MacAdam \leq 2 SDCM; CRI \geq 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 19° beam; UGR \leq 19; degree of protection IP20; PC1; 220-240 V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); converter included in canopy; canopy for through wiring; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Lighting calculator

