

# SASSO 40 round adjustable trimless soft acoustic ceiling

048-2820611M 048-2896197 002-90752



Project / Type

Notes

Count / Date



General
Ceiling   Recessed
tilt max 30°
rotation 360°
jet black   RAL 9005 <sup>1</sup>
Mounting set traffic white
front IP40   back IP20
403 lm
fixture 79 lm/W <sup>2</sup>

LED
4000 K
CRI ≥ 90
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 94   R <sub>r</sub> : 87   R <sub>l-15</sub> : 90
MR 0.86   MDER 0.78

Optical
medium   beam angle 25°
UGR ≤ 10
PstLM ≤ 1.0 <sup>3</sup>   SVM ≤ 0.4 <sup>3</sup>

Electrical
non DIM
PC2   220-240 V
system 6.2 W   fixture 5.1 W
12 Vf   450 mA


Physical
trimless
diameter 56 mm   height 50 mm

Cutout
diameter 58 mm
recessed depth 140 mm

<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses  
<sup>3</sup> Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; surface jet black; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; traffic white; for trimless installation in soft acoustic ceilings; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 25° beam; UGR ≤ 10; degree of protection from below IP40 (from above IP20); PC2; 220-240 V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



Installation instructions

Lighting calculator

