

SASSO 40 round adjustable trimless soft acoustic ceiling

048-2820419S 048-2896197 002-90753



Project / Type

Notes

Count / Date



| |
|------------------------------------|
| General |
| Ceiling Recessed |
| tilt max 30° |
| rotation 360° |
| gold dust RAL 260-M ¹ |
| Mounting set traffic white |
| front IP40 back IP20 |
| 375 lm |
| fixture 74 lm/W ² |

| |
|--|
| LED |
| 2700 K |
| CRI ≥ 90 |
| L85 / 50000 h |
| initial MacAdam ≤ 3 SDCM |
| R _g : 99 R _r : 91 R ₍₁₋₁₅₎ : 89 |
| MR 0.54 MDER 0.49 |

| |
|---|
| Optical |
| spot beam angle 14° |
| UGR ≤ 10 |
| PstLM ≤ 1.0 ³ SVM ≤ 0.4 ³ |


| |
|------------------------------|
| Electrical |
| DALI-2 |
| PC2 220-240 V |
| system 6.2 W fixture 5.1 W |
| 12 Vf 450 mA |

| |
|-------------------------------|
| Physical |
| trimless |
| diameter 56 mm height 50 mm |


| |
|-----------------------|
| Cutout |
| diameter 58 mm |
| recessed depth 140 mm |

¹ RAL code
² incl. consideration of optical losses & internal control unit losses
³ Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator

