

# SASSO 40 round downlight trimless soft acoustic ceiling

048-2800414S 048-2896197 002-90752



Project / Type

## Notes

Count / Date



## General

Ceiling | Recessed

rotation  $360^\circ$ 

matt silver

Mounting set traffic white

front IP44 | back IP20

367 lm

fixture 72 lm/W<sup>1</sup>

**LED**

2700 K

CRI  $\geq 90$

L85 / 50000 h

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 99 | R<sub>f</sub>: 91 | R<sub>{1-15}</sub>: 89

MR 0.54 | MDER 0.49

## Optical

spot | beam angle 15°

$$\text{UGR} \leq 10$$
$$\overline{\text{PstLM}} \leq 1.0^2 \mid \overline{\text{SVM}} \leq 0.4^2$$

## Electrical

non DIM

PC2 | 220-240 V

system 6.2 W | fixture 5.1 W

12 Vf | 450 mA

## Physical

trimless

diameter 56 mm | height 50 mm


## Cutout

diameter 58 mm

recessed depth 140 mm

<sup>1</sup> incl. consideration of optical losses & internal control unit losses<sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing

