



Project / Type

Notes

Count / Date



General
Showcase Recessed
white aluminium RAL 9006 ¹
IP20
Interior
218 lm
1260 lm/m
optical inset 79 lm/W ²

LED
3500 K
CRI ≥ 97
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 100 R _f : 97 R _{f(1-5)} : 96
MR 0.71 MDER 0.64


Optical
Opal opal (lambertsch)

Electrical
excl. driver
PC3 24 V
fixture 3.6 W
optical inset 2.8 W
21 W/m
24 V

Physical
length 200 mm width 9 mm height 9 mm

Miniature linear light inset made of aluminium; tubular design; surface lacquered in white aluminium; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); completely homogeneously illuminated, satinised PMMA cover; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² incl. consideration of optical losses