



Project / Type _____


Notes _____

Count / Date _____



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; asymmetric radiation characteristic; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Showcase | Standing _____

rotation 360° _____

white aluminium | RAL 9006 ¹ _____

IP20 _____

Interior _____

384 lm _____

optical inset 71 lm/W ² _____

LED

3500 K _____

CRI ≥ 95 _____

L80 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 101 | R_r: 96 | R_{f(1-5)}: 96 _____

MR 0.72 | MDER 0.66 _____

Optical

asymmetric _____

Electrical

excl. driver _____

PC3 | 24 V _____

fixture 8.1 W _____

optical inset 5.4 W _____

23 W/m _____

24 V _____

Physical

length 400 mm | width 9 mm | height 9 mm _____

¹ RAL code ² incl. consideration of optical losses