



Project / Type \_\_\_\_\_


Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



Miniature linear light inset made of aluminium; tubular design; surface lacquered in black; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); completely homogeneously illuminated, satinised PMMA cover; light colour 3500 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 97$ ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Showcase | Recessed \_\_\_\_\_

black | RAL 9021 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

Interior \_\_\_\_\_

1310 lm \_\_\_\_\_

1120 lm/m \_\_\_\_\_

optical inset 79 lm/W <sup>2</sup> \_\_\_\_\_

LED

3500 K \_\_\_\_\_

CRI  $\geq 97$  \_\_\_\_\_

L85 / 50000 h \_\_\_\_\_

initial MacAdam  $\leq 3$  SDCM \_\_\_\_\_

R<sub>g</sub>: 100 | R<sub>f</sub>: 97 | R<sub>f(1-5)</sub>: 96 \_\_\_\_\_

MR 0.71 | MDER 0.64 \_\_\_\_\_

Optical

Opal | opal (lambertsch) \_\_\_\_\_

Electrical

excl. driver \_\_\_\_\_

PC3 | 24 V \_\_\_\_\_

fixture 21.8 W \_\_\_\_\_

optical inset 16.5 W \_\_\_\_\_

19 W/m \_\_\_\_\_

24 V \_\_\_\_\_

Physical

length 1200 mm | width 9 mm | height 9 mm \_\_\_\_\_

<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses