



Project / Type

Notes

Count / Date



General

Showcase | Recessed

tar black | RAL 9021 <sup>1</sup>

IP20

Interior

466 lm

optical inset 73 lm/W <sup>2</sup>

LED

3500 K

CRI ≥ 95

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 101 | R<sub>f</sub>: 96 | R<sub>f(1-15)</sub>: 96

MR 0.72 | MDER 0.66

Optical

medium | beam angle 32°x46°

Electrical

excl. driver

PC3 | 24 V

fixture 9.5 W

optical inset 6.4 W


24 V

Physical

length 400 mm | width 9 mm | height 9 mm

Miniature linear light inset made of aluminium; tubular design; surface lacquered in tar black; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; precise radiation characteristic with 32°x46° beam; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses

Installation instructions

