



Project / Type


Notes

Count / Date



Miniature linear light inset made of aluminium; tubular design; surface lacquered in white aluminium; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3500 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 95$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; asymmetric radiation characteristic; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Showcase   Recessed
white aluminium   RAL 9006 <sup>1</sup>
IP20
Interior
412 lm
1180 lm/m
optical inset 64 lm/W <sup>2</sup>

LED

3500 K
CRI $\geq 95$
L80 / 50000 h
initial MacAdam $\leq 3$ SDCM
R <sub>g</sub> : 101   R <sub>r</sub> : 96   R <sub>f(1-5)</sub> : 96
MR 0.72   MDER 0.66

Optical

asymmetric
------------

Electrical

excl. driver
PC3   24 V
fixture 9.5 W
optical inset 6.4 W
27 W/m
24 V

Physical

length 400 mm   width 9 mm   height 9 mm
--

<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses