




Project / Type _____


Notes _____

Count / Date _____



Miniature linear light inset made of aluminium; tubular design; surface lacquered in black; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); completely homogeneously illuminated, satinised PMMA cover; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Showcase | Recessed _____

black | RAL 9021 ¹ _____

IP20 _____

Interior _____

873 lm _____

1130 lm/m _____

optical inset 79 lm/W ² _____

LED

3500 K _____

CRI ≥ 97 _____

L85 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 100 | R_f: 97 | R_{f(1-5)}: 96 _____

MR 0.71 | MDER 0.64 _____

Optical

Opal | opal (lambertsch) _____

Electrical

excl. driver _____

PC3 | 24 V _____

fixture 14.6 W _____

optical inset 11.0 W _____

19 W/m _____

24 V _____

Physical

length 800 mm | width 9 mm | height 9 mm _____

¹ RAL code ² incl. consideration of optical losses