



Project / Type

Notes

Count / Date



General
Showcase Recessed
black RAL 9021 ¹
IP20
Interior
823 lm
1100 lm/m
optical inset 64 lm/W ²

LED
3500 K
CRI ≥ 95
L80 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 101 R _r : 96 R _{f(1-15)} : 96
MR 0.72 MDER 0.66


Optical
asymmetric

Electrical
excl. driver
PC3 24 V
fixture 19.1 W
optical inset 12.8 W
26 W/m
24 V

Physical
length 800 mm width 9 mm height 9 mm

Miniature linear light inset made of aluminium; tubular design; surface lacquered in black; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; asymmetric radiation characteristic; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² incl. consideration of optical losses