

# NEVA disc 1200 light acoustic

suspended

091-3180538R 091-321210D



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



Acoustic element made of high quality, self-supporting, at least 50 % recycled PET felt with sound absorbing properties; round design; high quality visual and tactile surface with embossed pattern; absorption of direct sound and sound reflected from the ceiling; this creates high acoustic performance; pendant fitting with MITA circle 240 acoustic suspended (LUMINAIRE or BLIND SUSPENSION); LUMINAIRE: ring shaped luminaire housing in die-cast aluminium; extremely slim design; surface powder coated; suspended; with height adjustable rod suspension (chrome), feed in rod; electronic operating unit installed in the canopy; high gloss reflector with faceted design; energy-efficient LEDs with very good colour rendering; optionally with sensor

## Light distribution



## Product drawing



## General

jet black | RAL 9005 <sup>1</sup> \_\_\_\_\_  
marble grey \_\_\_\_\_  
IP20 \_\_\_\_\_  
1940 lm \_\_\_\_\_

## LED

3000 K \_\_\_\_\_  
CRI ≥ 80 \_\_\_\_\_  
L90 / 50000 h \_\_\_\_\_  
initial MacAdam ≤ 3 SDCM \_\_\_\_\_  
MR 0.56 | MDER 0.51 \_\_\_\_\_

## Optical

Reflector chrome | symmetric \_\_\_\_\_  
UGR ≤ 19 | ≥65° <1500 cd/m<sup>2</sup> \_\_\_\_\_  
PstLM ≤ 1.0 <sup>2</sup> | SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

## Electrical

DALI-2 | 1 DALI Addr. \_\_\_\_\_  
PC1 | 220-240 V \_\_\_\_\_  
system 13.7 W \_\_\_\_\_  
system 142 lm/W <sup>3</sup> \_\_\_\_\_

## Physical

rod 977 mm \_\_\_\_\_  
diameter 240 mm | height 45 mm \_\_\_\_\_

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. consideration of optical losses, internal control unit losses  
& operating device efficiency

