

NOBA 50

multi suspended
049-54131177W



Project / Type

Notes

Count / Date



Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; round ceiling surface mounted canopy (black or white) optionally for two to five lamps or two to ten lamps fittings; or linear ceiling surface mounted canopy (black or white) optionally for two to five lamps fittings; high quality plano-convex glass lens; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory



General

traffic white | RAL 9016 ¹

Cable traffic white

IP20

374 lm

LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 98 | R_f: 90 | R_[-15]: 88

MR 0.8 | MDER 0.72

Optical

wide flood | beam angle 67°

P_{stLM} ≤ 1.0 ² | SVM ≤ 0.4 ²

Electrical

PC3 | 220-240 V

system 3.3 W | fixture 2.4 W

system 113 lm/W ³ | fixture 153 lm/W ⁴


300 mA

Physical

diameter 50 mm | height 50 mm

cable length 2500 mm

Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	356	1.31
2	89	2.63
3	40	3.94
4	22	5.26
5	14	6.57

Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency
⁴ incl. consideration of optical losses & internal control unit losses





Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.964	0.923	0.884	0.847	0.811
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	18
B16	30
C10	23
C16	36

Mounting accessories

CANOPY multi linear

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
2-5 insets	traffic white	1000-34-50	005-2692037
2-5 insets	jet black	1000-34-50	005-2692038
2-5 insets	traffic white	1000-34-50	005-2692097
2-5 insets	jet black	1000-34-50	005-2692098



Mounting accessories

CANOPY WITH SLOTS multi round

TYPE	COLOUR	Ø (MM)	ARTICLE NUMBER(S)
2-5 insets	traffic white	380	005-2690037
2-5 insets	jet black	380	005-2690038
2-5 insets	traffic white	380	005-2690097
2-5 insets	jet black	380	005-2690098
2-10 insets	traffic white	380	005-2690137
2-10 insets	jet black	380	005-2690138
2-10 insets	traffic white	380	005-2690197
2-10 insets	jet black	380	005-2690198



Mounting accessories

CANOPY WITHOUT SLOTS multi round

TYPE	COLOUR	Ø (MM)	ARTICLE NUMBER(S)
2-5 insets	traffic white	380	005-2691037
2-5 insets	jet black	380	005-2691038
2-5 insets	traffic white	380	005-2691097
2-5 insets	jet black	380	005-2691098
2-10 insets	traffic white	380	005-2691137
2-10 insets	jet black	380	005-2691138
2-10 insets	traffic white	380	005-2691197
2-10 insets	jet black	380	005-2691198



NOBA 50

multi suspended
049-54131177W



Project / Type

Notes

Count / Date

Mounting accessories

HOOK surface

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
traffic white	16	030-1000017
jet black	16	030-1000018

