

NOBA 50

multi suspended
049-54130177W



Project / Type

Notes

Count / Date



Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; round ceiling surface mounted canopy (black or white) optionally for two to five lamps or two to ten lamps fittings; or linear ceiling surface mounted canopy (black or white) optionally for two to five lamps fittings; high quality plano-convex glass lens; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory



General

traffic white | RAL 9016 ¹

Cable traffic white

IP20

342 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99 | R_f: 90 | R_[-15]: 87

MR 0.6 | MDER 0.54

Optical

wide flood | beam angle 67°

P_{st}LM ≤ 1.0 ² | SVM ≤ 0.4 ²

Electrical

PC3 | 220-240 V

system 3.2 W | fixture 2.4 W

system 107 lm/W ³ | fixture 143 lm/W ⁴


300 mA

Physical

diameter 50 mm | height 50 mm

cable length 2500 mm

Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	325	1.31
2	81	2.63
3	36	3.94
4	20	5.26
5	13	6.57

Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency
⁴ incl. consideration of optical losses & internal control unit losses

