

# NOBA 40

multi suspended  
049-54109197W



Project / Type


Notes

Count / Date



Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; round ceiling surface mounted canopy (black or white) optionally for two to five lamps or two to ten lamps fittings; or linear ceiling surface mounted canopy (black or white) optionally for two to five lamps fittings; high quality plano-convex glass lens; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

## Light distribution



wide flood 69°

h (m)	EO <sup>2</sup> (lx)	ø (m)
1	288	1.37
2	72	2.74
3	32	4.12
4	18	5.49
5	12	6.86

## Product drawing



### General

rose gold

Cable traffic white

IP20

326 lm

### LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 97 | R<sub>f</sub>: 91 | R<sub>t(1-15)</sub>: 87

MR 0.52 | MDER 0.47

### Optical

wide flood | beam angle 69°

P<sub>stLM</sub> ≤ 1.0 <sup>1</sup> | SVM ≤ 0.4 <sup>1</sup>

### Electrical

PC3 | 220-240 V

system 3.3 W | fixture 2.4 W

system 99 lm/W <sup>2</sup> | fixture 133 lm/W <sup>3</sup>

300 mA

### Physical

diameter 40 mm | height 40 mm

cable length 2500 mm

<sup>1</sup> Value of containing product at full load (undimmed)  
<sup>2</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency  
<sup>3</sup> incl. consideration of optical losses & internal control unit losses

