



Project / Type _____

Notes _____

Count / Date _____



Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; round ceiling surface mounted canopy (black or white) optionally for two to five lamps or two to ten lamps fittings; or linear ceiling surface mounted canopy (black or white) optionally for two to five lamps fittings; high quality plano-convex glass lens; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory



General
traffic white | RAL 9016 ¹
Cable traffic white
IP20
326 lm


LED
2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R_g: 97 | R_f: 91 | R_{t(1-15)}: 87
MR 0.52 | MDER 0.47

Optical
wide flood | beam angle 69°
PstLM ≤ 1.0 ² | SVM ≤ 0.4 ²

Electrical
PC3 | 220-240 V
system 3.3 W | fixture 2.4 W
system 99 lm/W ³ | fixture 133 lm/W ⁴
300 mA

Physical
diameter 40 mm | height 40 mm
cable length 2500 mm

Light distribution



wide flood 69°

h (m)	EO° (lx)	ø (m)
1	288	1.37
2	72	2.74
3	32	4.12
4	18	5.49
5	12	6.86

Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency
⁴ incl. consideration of optical losses & internal control unit losses