



Project / Type _____

Notes _____

Count / Date _____



Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; round ceiling surface mounted canopy (black or white) optionally for two to five lamps or two to ten lamps fittings; or linear ceiling surface mounted canopy (black or white) optionally for two to five lamps fittings; high quality plano-convex glass lens; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory



General

brushed aluminium _____

Cable jet black _____

IP20 _____

352 lm _____

LED

4000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 98 | R_f: 90 | R_{f[1-15]}: 88 _____

MR 0.8 | MDER 0.72 _____

Optical

wide flood | beam angle 69° _____

PstLM ≤ 1.0 ¹ | SVM ≤ 0.4 ¹ _____

Electrical

PC3 | 220-240 V _____

system 3.3 W | fixture 2.4 W _____

system 107 lm/W ² | fixture 144 lm/W ³ _____


300 mA _____

Physical

diameter 40 mm | height 40 mm _____

cable length 2500 mm _____

Light distribution



wide flood 69°

h (m)	E0° (lx)	ø (m)
1	311	1.37
2	78	2.74
3	35	4.12
4	19	5.49
5	12	6.86

Product drawing



¹ Value of containing product at full load (undimmed)
² incl. consideration of optical losses, internal control unit losses & operating device efficiency
³ incl. consideration of optical losses & internal control unit losses