



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; round ceiling surface mounted canopy (black or white) optionally for two to five lamps or two to ten lamps fittings; or linear ceiling surface mounted canopy (black or white) optionally for two to five lamps fittings; high quality plano-convex glass lens; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory



**General**

brushed aluminium \_\_\_\_\_

Cable traffic white \_\_\_\_\_

IP20 \_\_\_\_\_

322 lm \_\_\_\_\_

**LED**

3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 2 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 | R<sub>f</sub>: 90 | R<sub>f[1-5]</sub>: 87 \_\_\_\_\_

MR 0.6 | MDER 0.54 \_\_\_\_\_

**Optical**

wide flood | beam angle 69° \_\_\_\_\_

P<sub>st</sub>LM ≤ 1.0 <sup>1</sup> | SVM ≤ 0.4 <sup>1</sup> \_\_\_\_\_

**Electrical**

PC3 | 220-240 V \_\_\_\_\_

system 3.2 W | fixture 2.4 W \_\_\_\_\_

system 101 lm/W <sup>2</sup> | fixture 135 lm/W <sup>3</sup> \_\_\_\_\_


300 mA \_\_\_\_\_

**Physical**

diameter 40 mm | height 40 mm \_\_\_\_\_

cable length 2500 mm \_\_\_\_\_

Light distribution



wide flood 69°

h (m)	EO <sup>2</sup> (lx)	ø (m)
1	285	1.37
2	71	2.74
3	32	4.12
4	18	5.49
5	11	6.86

Product drawing



<sup>1</sup> Value of containing product at full load (undimmed)  
<sup>2</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency  
<sup>3</sup> incl. consideration of optical losses & internal control unit losses