

NOBA 60 suspended canopy ceiling

049-53169198W 005-2601297



Project / Type

Notes

Count / Date



Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	727	1.31
2	182	2.63
3	81	3.94
4	45	5.26
5	29	6.57



General

rose gold

Cable jet black

IP20

765 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 97 | R_f: 91 | R_{t(1-5)}: 87

MR 0.52 | MDER 0.47

Optical

wide flood | beam angle 67°

Electrical

Casambi

PC3 | 220-240 V

system 6.4 W | fixture 4.8 W

system 120 lm/W ¹ | fixture 158 lm/W ²

150 mA

Physical

diameter 60 mm | height 60 mm

cable length 2500 mm

¹ incl. consideration of optical losses, internal control unit losses & operating device efficiency
² incl. consideration of optical losses & internal control unit losses

