



Project / Type _____

Notes _____

Count / Date _____



General

gun metal _____

Cable traffic white _____

IP20 _____

352 lm _____

LED

2700 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 99 | R_f: 90 | R_{f[1-5]}: 87 _____

MR 0.6 | MDER 0.54 _____

Optical

wide flood | beam angle 67° _____

PstLM ≤ 1.0 ¹ | SVM ≤ 0.4 ¹ _____

Electrical

PC3 | 220-240 V _____

system 3.2 W | fixture 2.4 W _____

system 110 lm/W ² | fixture 147 lm/W ³ _____

300 mA _____


Physical

diameter 60 mm | height 60 mm _____

cable length 2500 mm _____

Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; round ceiling surface mounted canopy (black or white) optionally for two to five lamps or two to ten lamps fittings; or linear ceiling surface mounted canopy (black or white) optionally for two to five lamps fittings; high quality plano-convex glass lens; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	335	1.31
2	84	2.63
3	37	3.94
4	21	5.26
5	13	6.57

Product drawing



¹ Value of containing product at full load (undimmed)
² incl. consideration of optical losses, internal control unit losses & operating device efficiency
³ incl. consideration of optical losses & internal control unit losses