

# NOBA 60 suspended canopy ceiling

049-53169137W 005-2601298



Project / Type

Notes

Count / Date



Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

## Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	727	1.31
2	182	2.63
3	81	3.94
4	45	5.26
5	29	6.57



### General

brushed brass  
Cable traffic white  
IP20  
765 lm

### LED

2700 K  
CRI ≥ 90  
L80 / 50000 h  
initial MacAdam ≤ 2 SDCM  
R<sub>g</sub>: 97 | R<sub>f</sub>: 91 | R<sub>t(1-15)</sub>: 87  
MR 0.52 | MDER 0.47

### Optical

wide flood | beam angle 67°

### Electrical

Casambi  
PC3 | 220-240 V  
system 6.4 W | fixture 4.8 W  
system 120 lm/W <sup>1</sup> | fixture 158 lm/W <sup>2</sup>  
150 mA

### Physical

diameter 60 mm | height 60 mm  
cable length 2500 mm

<sup>1</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses

