

# NOBA 50 suspended canopy ceiling

049-53139187W 005-2601238



Project / Type

Notes

Count / Date



Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

## Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	715	1.31
2	179	2.63
3	79	3.94
4	45	5.26
5	29	6.57



### General

jet black | RAL 9005 <sup>1</sup>

Cable traffic white

IP20

752 lm

### LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 97 | R<sub>f</sub>: 91 | R<sub>{1-15}</sub>: 87

MR 0.52 | MDER 0.47

### Optical

wide flood | beam angle 67°

PstLM ≤ 1.0 <sup>2</sup> | SVM ≤ 0.4 <sup>2</sup>

### Electrical

DALI-2

PC3 | 220-240 V

system 6.5 W | fixture 4.8 W

system 116 lm/W <sup>3</sup> | fixture 155 lm/W <sup>4</sup>

150 mA

### Physical

diameter 50 mm | height 50 mm

cable length 2500 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

<sup>3</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

<sup>4</sup> incl. consideration of optical losses & internal control unit losses

