

NOBA 50 suspended canopy trimless

049-53139178W 005-3511117 002-90810



Project / Type _____

Notes _____

Count / Date _____



Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	715	1.31
2	179	2.63
3	79	3.94
4	45	5.26
5	29	6.57



General

traffic white | RAL 9016 ¹ _____

Cable jet black _____

IP20 _____

752 lm _____

LED

2700 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 97 | R_f: 91 | R_{t(1-15)}: 87 _____

MR 0.52 | MDER 0.47 _____

Optical

wide flood | beam angle 67° _____

PstLM ≤ 1.0 ² | SVM ≤ 0.4 ² _____

Electrical

PC3 | 220-240 V _____

system 6.5 W | fixture 4.8 W _____

system 116 lm/W ³ | fixture 155 lm/W ⁴ _____

150 mA _____

Physical

diameter 50 mm | height 50 mm _____

cable length 2500 mm _____

Cutout

diameter 65 mm _____

¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency
⁴ incl. consideration of optical losses & internal control unit losses

