

# NOBA 60 suspended canopy trim

049-53169177W 005-3521117 002-90811



Project / Type


Notes

Count / Date



Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

## Light distribution



wide flood 67°

h (m)	EO° (lx)	ø (m)
1	727	1.31
2	182	2.63
3	81	3.94
4	45	5.26
5	29	6.57



## General

traffic white | RAL 9016 <sup>1</sup>

Cable traffic white

IP20

765 lm

## LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 97 | R<sub>f</sub>: 91 | R<sub>t(1-15)</sub>: 87

MR 0.52 | MDER 0.47

## Optical

wide flood | beam angle 67°

PstLM ≤ 1.0 <sup>2</sup> | SVM ≤ 0.4 <sup>2</sup>

## Electrical

PC3 | 220-240 V

system 6.4 W | fixture 4.8 W

system 120 lm/W <sup>3</sup> | fixture 158 lm/W <sup>4</sup>

150 mA

## Physical

diameter 60 mm | height 60 mm

cable length 2500 mm

## Cutout

diameter 65 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency  
<sup>4</sup> incl. consideration of optical losses & internal control unit losses

