

NOBA 50 suspended canopy trim

049-53139168W 005-3521117 002-90811



Project / Type _____
Notes _____
Count / Date _____



General

brushed aluminium
Cable jet black
IP20
752 lm

LED

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R_g: 97 | R_f: 91 | R_{t(1-15)}: 87
MR 0.52 | MDER 0.47

Optical

wide flood | beam angle 67°
PstLM ≤ 1.0 ¹ | SVM ≤ 0.4 ¹

Electrical

PC3 | 220-240 V
system 6.5 W | fixture 4.8 W
system 116 lm/W ² | fixture 155 lm/W ³
150 mA

Physical


diameter 50 mm | height 50 mm
cable length 2500 mm

Cutout

diameter 65 mm

Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	715	1.31
2	179	2.63
3	79	3.94
4	45	5.26
5	29	6.57

¹ Value of containing product at full load (undimmed)
² incl. consideration of optical losses, internal control unit losses & operating device efficiency
³ incl. consideration of optical losses & internal control unit losses