

049-53131158W 005-3521118 002-90810



Project / Type

## Notes

Count / Date



## General

gun metal

Cable jet black

IP20

819 lm

**LED**

4000 K

CRI  $\geq 90$

L80 / 50000 h

initial MacAdam  $\leq 2$  SDCM

R<sub>Q</sub>: 98 | R<sub>f</sub>: 90 | R<sub>{f1-15}</sub>: 88

MR 0.8 | MDER 0.72

## Optical

wide flood | beam angle 67°

$$\text{PstLM} \leq 1.0 \text{ } ^1 | \text{SVM} \leq 0.4 \text{ } ^1$$

## Electrical

PC3 | 220-240 V

system 6.5 W | fixture 4.8 W

system 126 lm/W<sup>2</sup> | fixture 169 lm/W<sup>3</sup>

150 mA

## Physical

diameter 50 mm | height 50 mm

cable length 2500 mm


## Cutout

diameter 65 mm

<sup>1</sup> Value of containing product at full load (undimmed)<sup>2</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency<sup>3</sup> incl. consideration of optical losses & internal control unit losses

Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

## Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	779	1.31
2	195	2.63
3	87	3.94
4	49	5.26
5	31	6.57