

049-53161148W 005-3521118 002-90810



Project / Type

Notes

Count / Date



General

chrome

Cable jet black

IP20

833 lm

LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 98 | R_f: 90 | R_{1-15}: 88

MR 0.8 | MDER 0.72

Optical

wide flood | beam angle 67°

$$\text{PstLM} \leq 1.0 \quad | \quad \text{SVM} \leq 0.4$$

Electrical

PC3 | 220-240 V

system 6.4 W | fixture 4.8 W

system 130 lm/W² | fixture 172 lm/W³

150 mA

Physical

diameter 60 mm | height 60 mm


cable length 2500 mm

Cutout

diameter 65 mm

¹ Value of containing product at full load (undimmed)² incl. consideration of optical losses, internal control unit losses & operating device efficiency³ incl. consideration of optical losses & internal control unit losses

Light distribution



wide flood 67°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 792 | 1.31 |
| 2 | 198 | 2.63 |
| 3 | 88 | 3.94 |
| 4 | 49 | 5.26 |
| 5 | 32 | 6.57 |