

NOBA 60 suspended canopy trimless

049-53160137W 005-3511117 002-90811



Project / Type _____


Notes _____

Count / Date _____



Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

Light distribution



wide flood 67°

| h (m) | EO ⁸ (lx) | ø (m) |
|-------|----------------------|-------|
| 1 | 757 | 1.31 |
| 2 | 189 | 2.63 |
| 3 | 84 | 3.94 |
| 4 | 47 | 5.26 |
| 5 | 30 | 6.57 |



General

brushed brass _____

Cable traffic white _____

IP20 _____

796 lm _____

LED

3000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 99 | R_f: 90 | R_[-15]: 87 _____

MR 0.6 | MDER 0.54 _____

Optical

wide flood | beam angle 67° _____

PstLM ≤ 1.0 ¹ | SVM ≤ 0.4 ¹ _____

Electrical

PC3 | 220-240 V _____

system 6.4 W | fixture 4.8 W _____

system 124 lm/W ² | fixture 165 lm/W ³ _____

150 mA _____

Physical

diameter 60 mm | height 60 mm _____

cable length 2500 mm _____

Cutout

diameter 65 mm _____

¹ Value of containing product at full load (undimmed)
² incl. consideration of optical losses, internal control unit losses & operating device efficiency
³ incl. consideration of optical losses & internal control unit losses

