

NOBA 50 suspended canopy ceiling

049-53139137W 005-2601297



Project / Type


Notes

Count / Date



Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

Light distribution



wide flood 67°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 715 | 1.31 |
| 2 | 179 | 2.63 |
| 3 | 79 | 3.94 |
| 4 | 45 | 5.26 |
| 5 | 29 | 6.57 |



General

brushed brass

Cable traffic white

IP20

752 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 97 | R_f: 91 | R_{t(1-15)}: 87

MR 0.52 | MDER 0.47

Optical

wide flood | beam angle 67°

Electrical

Casambi

PC3 | 220-240 V

system 6.5 W | fixture 4.8 W

system 116 lm/W¹ | fixture 155 lm/W²

150 mA

Physical

diameter 50 mm | height 50 mm

cable length 2500 mm

¹ incl. consideration of optical losses, internal control unit losses & operating device efficiency
² incl. consideration of optical losses & internal control unit losses

